

3800i Handheld Industrial Linear Imager



Features

Superior Read Range – imaging technology now extends the performance range out to 82 inches (208 cm) on linear codes. Long range reading performance eliminates the need to reach and climb to scan codes.

Fast and Aggressive Decode – Even on poorly printed or damaged codes, the 270 scans per second digital image logic is over 6 times faster than other technologies. Spend less time trying to re-scan poor codes and speed up the work process.

Rugged Packaging – An impact absorbing, shock resistant housing withstands fifty 6.5 foot (2 meter) drops, and is sealed to prevent dust, moisture, and other contaminants from entering the scanner. Designed to survive the most demanding industrial applications.

Durable – There are no moving parts to wear out and Hand Held Products backs this with an industry-leading 3 year warranty. Reliable performance year after year with no downtime.

Easy to Use – True point and shoot handheld ergonomics easily fits oversized gloved hands. Intuitive aiming means operators will become productive quickly.

The 3800i handheld industrial image readers are the first industrial class readers to bring you Hand Held Products industry-leading image technology. This technology allows you to read bar codes at ranges up to 82 inches (208 cm). In real world applications, this extended read range means less climbing and reaching, and more operator productivity.

Based on the proprietary image technology, the 3800i picks up your bar code image and processes its content 270 times per second. In a fraction of a second, the Hand Held Products digital image processor quickly and easily determines the data content and sends it to your host computer. This proprietary technology quickly and securely identifies poor quality symbols, and still delivers snappy performance.

We are so confident the 3800i image reader will withstand your industrial applications that we have backed it by a solid warranty. Every 3800i comes to you with a 3 year warranty against defects. Shock absorbing rubber overmold on the case and a sealed optics module ensure this device will survive dozens of 6.5 foot (2 meter) drops to concrete. Although we do not expect you to treat your reader this way, we know it will survive many years of accidental abuse.

Your industrial applications often take you into environments that challenge many devices. Your loading dock has extreme temperature variations, dirt, dust, and rain that will stress many bar code scanners. The 3800i is environmentally sealed to an IP54 rating, which prevents dust and water from entering the units and degrading performance. Sometimes you need to use this device outdoors during winter or other freezing temperature conditions. This imager withstands applications that subject it to constant -22°F (-30° C) temperatures and still survives.

For reading in applications that exhibit high ambient light, the 3800i can be ordered with an aiming beam, which offers true point and shoot performance without moving laser optics. This option allows the operator to reliably find and scan the code.

Contact your Hand Held Products representative at any of the locations listed on the back or visit us at www.handheld.com. See for yourself how Hand Held Products 3800i measures up!

3800i Specifications

Performance

| | |
|---------------------------------|---|
| Illumination: | 630 nM Visible Red LED |
| Receiving Device: | 3648 element linear imager |
| Reading Width: | 15 mil. code, 15 in. (38.1 cm) from nose, 10 in. (25.4 cm) wide |
| Resolution: | 7.5 mil. at 9 in. (22.9 cm) distance |
| Skew Angle: | ±65° |
| Pitch Angle: | ±65° |
| Horizontal Velocity: | 2 in. (5.1 cm) per second |
| Minimum Symbol Contrast: | 20% |
| Scan Rate: | Up to 270 scans per second |
| Decode Rate: | 270 decodes per second |

Ranges for the 3800i

| Narrow Width | Depth of Field (300 Lux Lighting) |
|--------------|-----------------------------------|
| 7.5 mil | 6.5 - 15 in. (16.5 - 38 cm) |
| 100% UPC | 2.5 - 28 in. (6.4 - 71 cm) |
| 15 mil | 2.5 - 31 in. (6.4 - 78.7 cm) |
| 20 mil | 1.5 - 42 in. (3.8 - 107 cm) |
| 55 mil | 4.0 - 82 in. (10.2 - 208 cm) |

Mechanical/Electrical


| | | |
|--------------------------------|------------------------|-----------------------------|
| Dimensions | <u>without aimer</u> | <u>with aimer</u> |
| Length: | 5.3 in. (13.5 cm) | 5.3 in. (13.5 cm) |
| Height: | 6.4 in. (16.3 cm) | 6.5 in. (16.5 cm) |
| Width: | 3.2 in. (8.1 cm) | 3.2 in. (8.1 cm) |
| Weight: | 7.5 oz. (213 g) | 8.4 oz. (238 g) |
| Housing: | UL 94V0 grade | |
| Power Requirements: | 4.5 - 14Vdc at scanner | |
| Current Draw (maximum): | <u>Input</u> | <u>Scanning</u> <u>Idle</u> |
| | 5V | 235mA 68mA |
| | 12V | 142mA 49mA |

Power Supply

Noise Rejection: Maximum 100mV peak to peak, 10 to 100 kHz

Environmental

| | |
|------------------------------|--|
| Temperature | |
| Operating: | -22°F to +122°F (-30°C to +50°C) |
| Storage: | -40°F to +140°F (-40°C to +60°C) |
| Humidity: | 0 to 95%, non-condensing |
| Sealing: | IP54 (water and dust resistant) |
| Mechanical Shock: | Operational after 50 drops from 6.5 ft. (2 m) to concrete |
| Ambient Illumination: | 0 - 70,000 lux |
| ESD Protection: | Functional after 15kV discharge |
| LED Classification: | Class 1 under EN60825-01 |
| Laser Classification | |
| Aimer Beam only: | Class 2 under 21 CFR 1040.10 and 1040.11 1mW max output, 650 nM, EN60825-1: 1994+A11+A2 |
| Vibration: | Withstands 5G peak from 22 to 300 Hz |
| Agency: | FCC Class B, CE EMC Class B, CE Low Voltage Directive, UL, cUL listed, TÜV |
| MTBF: | per MIL-HDBK-217F Ground Benign exceeds 100,000 hours without aimer, 91,000 hours with aimer |
| Symbologies: | Codabar, Code 39 including PARAF, Interleaved 2 of 5, Code 2 of 5, Matrix 2 of 5, Code 11, Code 93, Code 128, UPC, EAN/JAN, China Post, RSS. |
| Interfaces: | All popular PCs and terminals via keyboard wedge, keyboard replacement/direct connect, TTL level RS-232, TTL level Serial Wedge, USB, wand emulation, HHLC non-decoded laser compatible, True RS-232, IBM 468x, and IBM469x. |
| Warranty: | Three year factory warranty. |



Worldwide Offices

Offices Serving North America
 Skaneateles Falls, NY
 Tel: +1 315 685 8945
 or, in North America: +1 800 582 4263
 napresales@handheld.com
 Charlotte, NC
 Tel: +1 704 998 3998
 or, in North America: +1 800 582 4263
 napresales@handheld.com

Offices Serving Europe, Middle East, and Africa
Europe
 Tel: +31 (0) 40 29 01 800
 eupresales@handheld.com
United Kingdom
 Tel: +44 (0) 1 925 240055
 eupresales@handheld.com
Italy
 Tel: +39 (0) 2 67 100752
 eupresales@handheld.com

France
 Tel: +33 (0) 1 41 158220
 eupresales@handheld.com
Germany
 Tel: +49 (0) 7 477 151377
 eupresales@handheld.com
Spain
 Tel: +34 93 228 78 68
 eupresales@handheld.com

Offices Serving Asia and the Pacific Rim
Hong Kong
 Tel: +852 2511 3050
 appresales@handheld.com
Japan
 Tel: +813 5770 6312
 appresales@handheld.com
Shanghai
 Tel: +86 21 6361 3818
 appresales@handheld.com

Offices Serving Latin America
Naples, Florida
 Tel: +1 239 263 7600
 lapresales@handheld.com
São Paulo
 Tel: +55 11 2178 0500
 lapresales@handheld.com
Rio De Janeiro
 Tel: +55 21 2178 0500
 lapresales@handheld.com
Mexico
 Tel: +52 55 5203 2100
 lapresales@handheld.com

Web Site Address www.handheld.com
 Hand Held Products, Inc., ("Hand Held Products") © 1999-2006. All rights reserved. Printed in the U.S.A.
 Due to Hand Held Products' continuing product improvement programs, specifications and features herein are subject to change without notice.