

PowerScan® 7000BT SRI

Industrial Strength RF Imaging Scanner

Data Sheet



Features

- Solid state design makes the PowerScan 7000BT SRI the most rugged and reliable RF scanner on the market
- Bluetooth Wireless Technology with up to 328' / 100 m range
- Can be used with connectivity through the Base Station or directly to other Bluetooth devices
- Best dust and water sealing (IP65) on the market
- Industry leading standard range depth of field (DOF)
- Full multi-interface capability

Accessories

- Four-slot battery charger
- Scan stand
- Take-up reel
- Holster/fork lift mount
- PowerHood

Mechanical

Scanner

Dimensions: 8.0 x 3.0 x 4.5" / 203 x 76 x 115 mm
Weight: 13.5 oz / 383 g

Base Station (antenna down)

Dimensions: 9.4 x 4.6 x 1.9" / 239 x 117 x 48 mm
Weight: 12.6 oz / 358 g

Beeper/Speaker: 87 dBA for operator @ 50 cm (typical)

Environmental

Temperature Rating

Storage (Scanner/Battery): -4° to 140° F / -20 to 60° C
Storage (Base): -40° to 140° F / -40 to 60° C
Operating: -4° to 122° F / -20 to 50° C
Charging: 32° to 113° F / 0 to 45° C

Humidity: 5 to 95% NC

Shock: Withstands 50 drops from 6.5' / 2 m to concrete

Vibration: Meets MIL-STD-810E

Water & Particulate Sealing: IP65

Optical

Scanning Width: 2" wide at 1" from scanner; 6" wide at 7" from scanner

Minimum Resolution: 3 mil minimum element size

Skew (Yaw): ± 60°

Pitch: ± 65°

Roll: ± 40°

Depth of Field: See Depth of Field Table below

DEPTH OF FIELD Range Comparisons	
LABEL DENSITY	STANDARD RANGE
5 mil	3 to 6' / 76 to 15.2 cm
7.5 mil	2 to 16' / 51 to 40.6 cm
10 mil	15 to 22' / 3.8 to 55.9 cm
13 mil	1 to 30" / 2.5 to 76.2 cm
20 mil	1 to 42" / 2.5 to 106.7 cm
55 mil	2 to 80" / 51 to 203.2 cm

Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, ambient light, temperature, and scan angle dependant.

Electrical

Base Station requires Datalogic Scanning approved power supply

Battery Charge Times

In Base Station: Less than 4 hours

In Optional Charger: Less than 4 hours

Decoding Capability (autodiscriminates among)

- UPC/EAN/JAN
- P2 /P5 add-ons
- Code 39
- Micro PDF
- Code 128 ISBT
- Code 11
- RSS-14/Limited/Expanded (linear & stacked)
- Composites CC-A and CC-B (only RS composites)
- EAN 128
- MSI/Plessey
- Standard 2 of 5
- Code 128
- PDF-417
- IATA
- Italian Pharmacode 39
- Code 93
- Codabar
- Code 128 add-ons
- Interleaved 2 of 5

Host Communications

RS-232, Keyboard Wedge, USB, Wand Emulation, IBM 46XX, and USB (IBM SurePos).

In addition to standard PC/AT/PS/2, the keyboard wedge interface supports the following: Wyse 55, 60, 120, 150, etc.; IBM 347X/3487/31XX; Digital VT220, 240, 320, 420, 510, 520; Sun 420, ITX, and Sparc 5/10.


Safety & Regulatory

Electrical: Complies to UL; cUL; EN60950

Emissions: Complies to FCC; EN 55022; CISPR22

Radio: FCC Part 15C, R and TTE, and IC

Laser Classification: CDRH Class II,

 (Caution: Laser Radiation - do not stare into beam); IEC 60825 Class 2

Restriction of Hazardous Substances: Complies to EU RoHS



The Bluetooth® word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Datalogic Scanning Inc. is under license.



Datalogic Scanning, Inc.

Toll free: 1 800 695 5700

International: 1 541 683 5700

E-mail us at: scanning@datalogic.com

www.datalogic.com



Copyright © Datalogic Scanning, Inc. 2006-2007. All rights reserved. Protected to the fullest extent under U.S. and international laws. Copying, or altering of this document is prohibited without express written consent from Datalogic Scanning, Inc. • Datalogic Scanning, Inc. of Eugene, Oregon, USA is ISO registered by NQA. • The Datalogic logo is a trademark of Datalogic SpA. • All brand and product names are trademarks of their respective owners. • Additional information concerning this product or other Datalogic products and services can be found at the Datalogic web site: www.datalogic.com. • Product specifications are subject to change without notice.