

QuickScan® QS6000 Plus

Handheld Scanner

Data Sheet



Ideal for:

- Retail Applications
- Health Care
- Inventory
- Office Automation
- Light Industrial

Features:

- Great depth-of-field
- AutoSense® stand for hands-free operation
- Optional EAS antenna for simultaneous scanning and security tag deactivation
- Universal wedge for additional keyboard emulation, bar code symbologies, and data editing
- Sunrise 2005 Compliant
- RSS decoding available on select models

Mechanical

Dimensions

Height: 6.5" / 16.5cm
 Width: 2.8" / 7.1cm
 Length: 4.2" / 10.7cm

Weight: 6.0 oz. / 184 g (scanner)

Environmental

Temperature Rating

Operating: 32° to 122° F / 0° to 50°C
 Storage: -40° to 158° F / -40° to 70° C

Humidity: 5 to 95% NC

Shock (at 23° C): Withstands multiple 5' / 1.5m drops onto concrete (100+ drops to countertop)

Water & Dust: Resistant, IEC529 rating IP53DW

Vibration: MIL-STD-810E

Optical

Light Source: 650nm Visible Laser Diode (VLD)

Scan Rate: 42 scans/sec (nominal)

Scan System: Electromagnetic dithering mirror

Resolution: 5 mils (13mm)

Print Contrast: 30% minimum

Pitch: ±65°

Skew: ±55°

Scan angle: 46°

Ambient Light Immunity

Artificial Light: 1,200 foot candles / 12,900 Lux

Sunlight: 8,000 foot candles / 81,600 Lux

Depth of Field: Refer to Chart below

DEPTH OF FIELD* Range Comparisons	
LABEL DENSITY	RANGE
5 mils	10 — 30" / 2.5 — 7.6 cm
7.5 mils	0.5 — 6.0" / 13 — 15.2 cm
10 mils	0 — 9" / 0 — 22.9 cm
13 mils	0 — 13" / 0 — 33 cm
20 mils	Up to 20" / Up to 50.8 cm

* Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.

Electrical

Operating Voltage

Undecoded: 4.2 V to 14 VDC

Decoded: 4.5 V to 14 VDC

Operating Current - nominal

Undecoded: 70 mA to 5 VDC

Decoded: 120 mA to 5 VDC

Idle Current - nominal

Undecoded: 10 µA to 5 VDC

Decoded: 23 mA to 5 VDC

Decoded lowest power mode: 14 mA to 5 VDC

Communications

- RS-232
- Standard Keyboard Wedge
- Universal Keyboard Wedge
- IBM 46XX
- USB
- Wand Emulations
- OCIA
- Undecoded

Decoding Capability

- UPC A, E / EAN 8, 13 / JAN 8, 13 (Add-ons P2/P5)
- Code 128 / EAN 128
- Pharmacoce 39
- Interleaved 2 of 5
- Code 39
- RSS on selected models
- Codabar
- Code 93
- Standard 2 of 5
- IATA
- MSI/Plessey

Safety & Regulatory

Electrical: Complies to Gost R; TÜV; UL; cUL

Emissions: Complies to FCC-A; EN 55022-B; BCIQ CNS 13438; AS/NZS 3548; VCCI-B

Laser Classification: CDRH Class IIa;

(Caution: Laser Radiation - do not stare into beam); IEC 60825 Class 1 & 2



Available Mounting Options



P/N: 7-0204
AutoSense®

P/N: 7-0470
AutoSense®
(w/o base)

P/N: 5-0788
Universal Holster

P/N: 7-0393
Mountable
Tabletop



Copyright © PSC Inc. 1998-2005. All rights reserved. • Protected to the fullest extent under U.S. and international laws. Copying or altering of this document is prohibited without express written consent from PSC. • PSC, QuickScan and the PSC logo are registered trademarks of PSC Inc. • All other brand and product names are trademarks of their respective owners. • Additional information concerning this product or other PSC products and services can be found at the PSC web site: www.psc.com. • Product specifications are subject to change without notice.



PSC Inc.
 959 Terry Street
 Eugene OR 97402-9150 USA
 Tel: 800 695 5700 or 541 683 5700
 Fax: 541 345 7140