

QuickScan® QS2500

Data Sheet

Linear Imager



Mechanical

Dimensions
 Height: 7.3" / 18.5 cm
 Width: 2.9" / 7.4 cm
 Length: 4.5" / 11.4 cm
Weight: 6.3 oz. / 179 g (cable not included)

Environmental

Temperature Rating:
 Operating: 32° to 113° F / 0° to 45° C
 Storage: -22° to 149° F / -30° to 65° C
Humidity:
 Operating: 5 to 95% NC

Shock: Withstands ten 5.0' (1.5m) drops to concrete
Water & Dust: Resistant, IEC 60529 rating IP42DW
ESD protection: Functional after 15kV discharge

Optical

Light Source: 660nm Visible Red Diode
Scan Rate: 200 scans/sec
Scan Width: 4.0"/10.2 cm at 5.0"/12.7 cm from label
Resolution: 5 mils / 0.13mm
Print Contrast: 25% or higher
Pitch: ±60°
Skew: ±75°
Scan angle: 46°

Ambient Light Immunity
 Artificial Light: 6,968 foot candle / 75,000 Lux
 Sunlight: 6,968 foot candle / 75,000 Lux
Depth of Field: Refer to table below

DEPTH OF FIELD*	
Range Comparisons	
LABEL DENSITY	RANGE
5 mils	1.0" - 4.5" / 2.5 - 11.4 cm
10 mils	0.05" - 8.5" / 1.3 - 21.6 cm
13 mils (100% UPC)	0.5" - 11" / 1.3 - 28.0 cm
20 mils	1.0" - 16" / 2.5 - 40.6 cm
40 mils	2.0" - 28.0" / 5.0 - 71.0 cm

* Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.

Electrical

Operating Current:
 Operating: 225 mA @ 5 VDC
 Standby: 100 mA @ 5 VDC

Communications


- RS-232
- Keyboard Wedge
- Wand Emulation
- USB
- IBM 46XX
- IBM USB

Decoding Capability (autodiscriminates)

- UPCA, E / EAN 8, 13 / JAN 8, 13 (Including add-ons P2/P5)
- Code 128
- Pharmacode 39
- Codabar
- Industrial 2 of 5
- RSS-14
- RSS Expanded
- MSI/Plessey
- Telepen
- Code 11
- Code 93
- Code 39
- Interleaved 2 of 5
- Matrix 2 of 5
- RSS-14 Stacked
- RSS Limited
- UK/Plessey
- Code 16K
- PDF417 with audio assist

Safety & Regulatory

Electrical: Complies to UL and cUL
Emissions: Complies to FCC-A; EN 55022-B; VCCI-A
Laser Classification: CDRH Class IIa;
 (Caution: Laser Radiation - do not stare into beam);
 IEC 60825 Class 1 & 2



Ideal for:

- Retail applications
- Health care
- Inventory
- Office automation
- Document tracking
- Light industrial

Features:

- Aggressive reading and an extended depth-of-field
- Reads Reduced Space Symbology (RSS), PDF417 and linear codes for flexibility
- Ergonomic "aim and shoot" design
- Reliable and durable, providing long lasting performance

Accessories



P/N: 7-0803 (Gray);
 P/N: 7-0832 (Black)
 Hands Free Stand

P/N: 7-0393
 Tabletop or
 Wall Mount

PSC Inc.
 959 Terry Street
 Eugene, OR 97402-9150 USA
 Tel: 800 695 5700 or 541 683 5700
 Fax: 541 345 7140



Copyright © PSC Inc. 2002-2005. All rights reserved. Protected to the fullest extent under U.S. and international laws. Copying or altering of this document is prohibited without express written consent from PSC. PSC, QuickScan and the PSC logo are registered trademarks of PSC Inc. All other brand and product names are trademarks of their respective owners. Additional information concerning this product or other PSC products and services can be found at the PSC web site: www.psc.com. Product specifications are subject to change without notice.

